

Horizontal baling press



JAM trading e. K.

type	1410-22/50	1410-30/60	1410-37/70	1410-45/80	1810 - 55/80	1810-90/80	1810-90/100	1810 – 110/100	2010-110/130	2012-110/150	2012-110/170	
machine length	8,300 mm				11,000 mm				13,629 mm			
machine width	2,200 mm				2,350 mm				4,610 mm			
machine height	3,800 mm				3,920 mm				4,945 mm			
empty weight	appr. 13,000 kg	appr. 13,2000 kg	appr. 13,500 kg	appr. 14,000 kg	appr. 23,000 kg	appr. 23,500 kg	appr. 24.000 kg	appr. 24,500 kg				
electric hyd. power	22 kW	30 kW	37 kW	45 kW	1 x 55 kW	2 x 45 kW	2 x 45 kW	2 x 55 kW	2 x 55 kW	2 x 55 kW	2 x 55 kW	
pressing force	500 kN	600 kN	700kN	800 kN	800 kN	800 kN	1,000 kN	1,000 kN	1,300 kN	1,500 kN	1,700 kN	
channel adjustment	automatic				automatic				automatic			
binding	4 times vertical				4 times vertical				4 times vertical			
filling opening dimension	1,400 x1,000 mm				1,800 x1,000 mm				2,000 x1,000 mm			
Bale size	1,100 x 700 mm, length adjustable				1,100 x 750 mm, length adjustable				1,200 x 1,100 mm, length adjustable			
bale weight (depending on material and dimension)	up to 450 kg	up to 500 kg	up to 550 kg	up to 600 kg	up to 600 kg	up to 600 kg	up to 700 kg	up to 700 kg	500 – 1,100 kg			
cycletime (empty)	20 sec.	14 sec.	10 sec.	12 sec.	18 sec.	9 sec.	11 sec.	11 sec.	18 sec.	22 sec.	26 sec.	
capacity (empty)	180 m³/h	260 m³/h	360 m³/h	300 m³/h	270 m³/h	540 m³/h	440 m³/h	440 m³/h	990 m³/h	950 m³/h	820 m³/h	
capacity	max. 7 t/h	max. 10 t/h	max. 15 t/h	max. 18 t/h	max. 9 t/h	max. 18 t/h	max. 22 t/h	max. 25 t/h	max. 30 t/h	max. 35 t/h	max. 40 t/h	